

MISURE / MEASURES

| Modello Model | ØA | B | C |
|------------------|-----|-------|-------|
| | mm | mm | mm |
| * 100 | 98 | 177 | 238 |
| * 125 | 122 | 217 | 262,4 |
| * 150 | 147 | 244 | 293,4 |
| * 200 | 197 | 278,5 | 353,6 |

CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTICS

| Modello / Model | 100 | 125 | 150 | 200 |
|----------------------|------|------|---------|---------|
| V | 230 | 230 | 230 | 230 |
| W | 25 | 25 | 80 | 75 |
| R.P.M. | 2200 | 2100 | 2700 | 2700 |
| m ³ /h | 130 | 320 | 420/560 | 720/910 |
| m.m.H ₂ O | 14 | 23 | 26/36 | 14/30 |
| Ø mm | 100 | 125 | 150 | 200 |
| kg | 1,2 | 2,1 | 3,2 | 4,5 |
| dB | 14 | 25 | 31/39 | 34/39 |


PREZZI / PRICES

| € | - | - | - | - |
|---|---|---|---|---|
|---|---|---|---|---|





REGOLATORE VELOCITÀ / SPEED REGULATOR

| Modello / Model | € |
|-----------------|---|
| RC2A | - |

DIMENSIONI / DIMENSIONS



DATI PRESTAZIONALI / PERFORMANCE DATA

**Caratteristiche:**

Potente estrattore tubolare per installazione in condotta rigida e flessibile. Facile installazione. Silenzioso.

Characteristics:

Powerful tubular extractor for installation in rigid and flexible pipes. Easy installation. Silent.